

	contains	m ²	ft ²	weight
1 pack cadenza	9 planks	2,66 m ²	28.67 ft ²	19,4 kg
1 pallet cadenza	56 packs	149,16 m ²	1605.60 ft ²	1098 kg

product specifications

dimensions mm / inch	1383 x 214 mm / 54.45" x 8.43"
total thickness mm / inch	8 mm / 0.31"
bevels	4
loc system	duoloc
level of use according to European standard EN10874	23 heavy domestic use
	32 general commercial use
residential warranty	20 years
commercial warranty	3 years

composition



surface layer	direct laminated paper, impregnated with melamine resin
substrate	moisture resistant High Density Fiberboard (HDF)
backing	direct laminated paper, impregnated with melamine resin

test results

abrasion resistance	EN13329	AC4 (IP≤4000)
impact resistance	EN13329	Small ball : ≤ 12 N - Big ball : ≤ 750 mm
thickness swelling	EN13329	≤ 18 %
fire resistance	EN14041	Cfl-S1
formaldehyde emission	EN14041	E1
slip resistance	EN14041	DS
density	EN323	900 kg/m ³
resistance to staining	EN438	5 (groups 1+2); 4 (group 3)
effect of a furniture leg	EN424	no damage (foot type 0)
effect of a castor chair	EN425	no change in appearance or damage
thermal resistance in combination with underlay Excellence Plus	ISO 8302	0,08 m ² K/W – Suitable for floor heating/cooling. Detailed instructions on www.berryalloc.com



*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).



product leaflet
installation manual
warranty conditions
care&maintenance
floor heating manual
underlay guide

