

Version: 23/03/2020

	contains	m <sup>2</sup>	ft <sup>2</sup>	weight
1 pack Style planks	8 planks	2.16 m <sup>2</sup>	23.24 ft <sup>2</sup>	13.8 kg
1 pallet Style planks	56 packs	120.96 m <sup>2</sup>	1301.53 ft <sup>2</sup>	774 kg





## product specifications

			plank
Dimensions	EN ISO	24346	1326 x 204 mm
Total thickness	EN ISO	24346	5 mm
Thickness of the wear layer	EN ISO	24340	0,55 mm
Total weight	EN ISO	23997	6.93 kg/m <sup>2</sup>
Surface treatment			PUR
Usage classification	EN ISO	10874	23-33-42
Residential warranty			lifetime
Commercial warranty			10 years

## test results

Underfloor heating	EN ISO	12524	suitable max 27°C (80°F)/ electrical floorheating systems max 60 W/m <sup>2</sup>
Castor chair	EN ISO	4918	pass
Fire resistance	EN ISO	13501-1	Bfl-s1
Chemical resistance	EN ISO	26987	OK
Thermal resistance	EN ISO	8302	0,0293 m <sup>2</sup> K/W
Residual indentation	EN ISO	24343-1	< 0,10 mm
Slip resistance	DIN	51130	R10
	EN ISO	13893	Class DS
RRL pendulum test: dry	CEN/TS	15676	66.5
RRL pendulum test: wet	CEN/TS	15676	59.7
Sound reduction: impact sound	EN ISO	717-2	11 dB
Reflected walking sound	EN ISO	16205	54.4 dB
Light fastness	EN ISO	105-B02	>6
Dimensional stability	EN ISO	23999	≤ 0,05 %
Antistatic	EN ISO	1815	yes
Formaldehyde	EN ISO	717-1	E1
VOC emission			Indoor air comfort GOLD





1. Protective PU lacquer
2. Wear layer 0,55 mm
3. Decor layer
4. Rigid Composite Board (RCB)  
with DreamClick locking elements