

Installation instruction

Article no.:

PrimaCover Paint

Multifunctional painter's fleece with solid non-slip PE foil on the underside

- Liquid-proof
- Anti-slip
- Absorbent

Application range

- For covering flat, hard surfaces when working indoors, protects the substrate from mechanical damager and moisture.
- Not suitable for porous surfaces.
- ♦ Not suitable for wet or freshly laid floors. Risk of waterlogging and associated negative changes to the floor.

Installation instruction

- The substrate must be clean, dry, pressure-resistant, dust- and grease free.
- Existing floor heating must be switched off.
- ♦ Lay the non-woven on the floor and fix the edges and corners with a suitable tape.
- Cut the non-woven at edges and corners with a safety knife.
- Don not lay over cables, protruding objects or other elevations, trip hazard!
- When laying several sheets next to each other, allow them to overlap by 10cm, press firmly and, if necessary, fix with a suitable tape.
- Check the surface of the board regularly and clean if necessary
- ♦ If the non-woven is damaged, remove it and lay out new fleece, this is the only way to ensure reliable protection of the substrate.

Re-usability

- Test the suitability of the product in advance in an inconspicuous place.
- Before re-use, check the underside for dirt and remove if necessary.

Note

- Test the suitability of the product in advance.
- No acceptance of liability for incorrect usage.
- ♦ It is absolutely necessary to pay attention to the installation instructions and application range!
- Always store in a dry place!

♦ 3 Months after installation, the non-woven should be removed from the surface. It is recommended to protect the nonwoven from high temperatures and strong direct sunlight, as this could affect its technical characteristics.

Disposal

The non-woven can de disposed of in landfills after use, with dried paint or plaster residues, in compliance with official regulations.



900041, 900042, 900043